


# BOSA

SURFACE  
IP54 / IK06



LED			IP54	IK06				5 years warranty	50,000 hrs L80/B10 Ta=25°C	220-240V 50-60Hz		CE
-----	--	--	------	------	--	--	--	------------------	----------------------------------	---------------------	--	----

## BOSA

BOSA  
Surface

LIGHT OUTPUT	up to 8600 lm
EFFICIENCY	up to 128 lm/W
WIRING	ECG, on request: DALI, 1-10V Sensor (Tridonic, Hytronic) On request: Emergency kit (1h, 3h, exclude 20W, 27W)
CCT	3000 - 4000K
CRI	≥ 80 Ra
MATERIALS	
> Housing	Sheet steel
> Diffuser	Opal Polycarbonate
> End caps	ABS
LIGHT DISTRIBUTION	Direct
ADVANTAGES	Impact-resistant (IK06)
SURFACE FINISH	White color (RAL9003); other colors on request
ACCESSORIES	Cable gland for end cup PG 11 (purchase code: CG-PG11)




ELEGANT OPAL ABS END CAPS



OPAL POLYCARBONATE (PC)

drawing #1



Net lumen output	CCT	Power	Dimensions A	Weight	Purchase code
(lm)	(K)	(W)	(mm)	(kg)	
2300	3000	20	612	2.01	BOSA.60.20.2300.3K.54
2500	4000	20	612	2.01	BOSA.60.20.2500.4K.54
3100	3000	27	612	2.01	BOSA.60.27.3100.3K.54
3300	4000	27	612	2.01	BOSA.60.27.3300.4K.54
4600	3000	36	1172	2.54	BOSA.120.36.4600.3K.54
4900	4000	36	1172	2.54	BOSA.120.36.4900.4K.54
6400	3000	52	1172	2.54	BOSA.120.52.6400.3K.54
6700	4000	52	1172	2.54	BOSA.120.52.6700.4K.54
5900	3000	45	1452	3.65	BOSA.150.45.5900.3K.54
6300	4000	45	1452	3.65	BOSA.150.45.6300.4K.54
8000	3000	67	1452	3.65	BOSA.150.67.8000.3K.54
8600	4000	67	1452	3.65	BOSA.150.67.8600.4K.54